



Built-in, commercial overflow spas should be standard in all hotels and public areas.

The Round 2 overflow spa, with a diameter of 2 metres, can comfortably seat up to 5 people. With its strategically positioned jets, it offers many massage options for different parts of the body and showcases the benefits of chromotherapy.

Overflow spas can be used privately, as well as commercially, as they provide full comfort thanks to their continuous water level and ease of installation.

## COMMERCIAL RANGE

### ROUND 2





# COMMERCIAL RANGE

## ROUND 2

General Specifications	
Dimensions	Ø 205 (± 1cm)
Positions (Seats / Loungers)	5 (5 / -)
Water capacity (Litre)	680 l
Empty spa weight / Full spa weight	340 Kg / 1,750 Kg
Material	Acrylic

Features	
Jets	20
Air nozzles	10
Chromotherapy LED	Yes
Metallic structure	Yes
Light	Yes
Digital control panel	Yes

Options	
Insulated cover	Optional

Compact Kit	Digital
Filter	Ø 500
Filtration Pump	0.60 KW
Massage Pumps	2 KW
Air Blower	0.9 KW
Standard heater power	3 KW
Buttons / Control	Digital panel
Power requirement Low Amp (W)	9,362 W
Power requirement (A)	15.7 A
Voltage	230 V
Ozonater	Optional

We reserve the right to modify the characteristics of our products without prior notice.