HAYWARD®

The secret for a successful pool

www.hayward.fr/en

CONTINUE THE EXPERIENCE ON:

facebook.com/hayward.fr

HaywardPoolEurope

ONLINE SERVICES
Free extended warranty
Free subscription to the newsletter
The heat pump configurator
Online savings simulator
On-line expert
Spare parts catalogue

REMOTE CONTROL YOUR POOL

AUTOMATION

AquaRite +

Hayward is launching an innovative device to control swimming pool equipment (including filtering cycles and water temperature) and manage water treatment (pH levels and chlorine generation).

The sleek and innovative design of AquaRite + includes a detachable screen for ease of monitoring. And in response to new nomadic lifestyles AquaRite + can be used to control equipment remotely.

The Advantages

+ Monitor and manage filtering equipment.

+ Continuously treat and regulate water quality using salt chlorination.

+ Remotely control installation.

Included	Optional			
Hayward chlorinator cell	pH probe	ORP probe	Detachable screen for remote monitoring and control	Wifi module

Equipment Control

Control filtering cycles

Control heating equipment

Control lighting

Control additional equipment

Water treatment control

Control salt chlorination

Control pH

Control redox

2 YEARS WARRANTY + 1 YEAR (1)

Naturally Hayward

NEW

PERFORMANCE AND RELIABILITY

▶ Continuously control salt chlorination of the water for optimum treatment without adding chlorine tablets.

▶ Uses Hayward's Turbo-Cell, recognised as the most reliable on the market.

PRECISION

▶ Control all of the filtering, heating, and lighting equipment for precise, bespoke management of the installation.

MULTIPURPOSE

▶ Can control up to 7 pieces of equipment.

▶ 4 filtering modes available (manual, automatic, intelligent, and smart) for more flexible use.

Description	AQR-PLUS-T3E	AQR-PLUS-T9E	AQR-PLUS-T15E	AQR-PLUS-LSE
Wifi module	AQR-PLUS-WIFI (optional)			
Principal control outputs	Filtering / Lighting / Heating			
Additional control outputs	4 additional relay outputs to be programmed by the user			
Salinity	3,2 g/L	3,2 g/L	3,2 g/L	1,5 g/L
Pool in m³	60 m³	95 m³	150 m³	60 to 90 m³**
Chlorine production	10 g/h	20 g/h	30 g/h	15 g/h
pH regulator	Yes			
ORP regulator	Optional			Provided
Display	2,8" TFT			
Power supply	220 V 50/60 Hz			
Max consumption	-*			
Dimensions	270 * 220 * 115 mm			
Electronic control	Black fireproof plastic			
Protection cover	White ABS plastic			
Salinity test	by reverse polarity			
Display salt concentration	Detects g/l of salt (precise to within +/- 10%)			
Safety cover closed	Production can be set from 0-100% depending on whether the pool cover is open or closed			

(1) 2 years warranty + 1 year extra when the product is purchased from a Totally Hayward dealer.

* Data subject to change   ** Depending upon geographical zone

Smart System

PUMPS   FILTERS   LIGHTING   WATER TREATMENT   AUTOMATION   CLEANERS   HEAT PUMPS